

Uncontrolled document as of July 7, 2010. Refer to website for up to date specifications.

LIGHTS
3610
 Little Ed Recoil LED



Little Ed™ 3610 Recoil™ LED Flashlight

The 3610 uses a 1 watt LED that's aimed backwards into the reflector. 100% of the light is captured and aimed forward as a tight collimated beam that's as bright as an incandescent. The body is made of tough ABS resin that's corrosion proof and resistant to extreme temperatures. It is powered by 4 AA alkaline cells (included).

Minimum Pack 1 ea.
 Packaged Weight: 11.1 oz.



Little Ed™ 3610 Recoil™ LED Flashlight Configurations

Cat. #	Description
3610	Little Ed™ 3610 Recoil™ LED Flashlight (Carded)
3610PL	Little Ed™ 3610 Recoil™ LED Flashlight w/ Photoluminescent Shroud



Little Ed™ 3610 Recoil™ LED Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Recoil LED	72.0	2,622
Batteries	Battery Burn Time	Battery Pack/Charging Time
4 AA Alkaline (Included)	7.25 hrs.	N/A
Watts	Voltage	
1	6	
Length	Weight w/Batteries	Weight w/o Batteries
7.51" (19.1 cm)	10.5 oz. (0.3 kg)	6.9 oz. (0.2 kg)

Little Ed™ 3610 Recoil™ LED Flashlight Approvals

IECEx	ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T83°C Da IP66
UL	Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4

Little Ed™ 3610 Recoil™ LED Flashlight Accessories

Cat. #	Description	Sug. Retail
2413PL	Photoluminescent Shroud	US\$8.95

Pelican™ Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com