

Uncontrolled document as of July 7, 2010. Refer to website for up to date specifications.



SabreLite™ 2000 Photoluminescent Flashlight

Same features as the SabreLite™ 2000 Flashlight but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures.

Minimum Pack 6 ea.
Packaged Weight: 6.8 oz.



Submersible

SabreLite™ 2000 Photoluminescent Flashlight Configurations

Cat. #	Description
2000PL	SabreLite™ 2000 Photoluminescent Flashlight (Carded)








Yellow

SabreLite™ 2000 Photoluminescent Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
Xenon	33.0	10,000
Batteries	Battery Burn Time	Battery Pack/Charging Time
3 C Alkaline (Not included)	5 hrs.	N/A
Watts	Voltage	
3.3	4.5	
Length	Weight w/Batteries	Weight w/o Batteries
7.79" (19.8 cm)	12.8 oz. (0.36 kg)	5.31 oz. (0.15 kg)

SabreLite™ 2000 Photoluminescent Flashlight Approvals

	Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.
	Class I, II, Div. 2; Gp. ABCD/G , T3C.
	Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C
	10C-629-2
	IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67

SabreLite™ 2000 Photoluminescent Flashlight Accessories

Cat. #	Description	Sug. Retail
2004	SabreLite™ 2000 Lamp Module	US\$13.50

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com