

Uncontrolled document as of July 7, 2010. Refer to website for up to date specifications.

**LIGHTS**  
**2000**  
**SabreLite**



**SabreLite™ 2000 Flashlight**

This powerful flashlight was designed with one thing in mind: SAFETY. It carries more approvals than any other flashlight on the market today, making it safe for any hazardous environment or condition. The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. Unlike ordinary flashlights that produce a yellow beam, the SabreLite's incredibly bright Xenon lamp produces a powerful collimated white beam. Pelican's SabreLite is the leader in quality and performance.



Submersible

**NSN List**

| NSN #            | Description        |
|------------------|--------------------|
| 6230-01-281-3775 | 2000B Black        |
| 6230-01-295-1259 | 2000B Yellow       |
| 6230-01-324-2951 | 2000B Orange       |
| 6230-01-496-3640 | 2000 Zone 1 (Peli) |
| 6240-01-493-6640 | 2004 Lamp Module   |

Minimum Pack 6 ea.  
Packaged Weight: 6.8 oz.  
Assorted Packs available - 2 black, 2 yellow, 2 orange.

**SabreLite™ 2000 Flashlight Configurations**

| Cat. # | Description  |
|--------|--|
| 2000   | SabreLite™ 2000 Flashlight (Carded)                            |
| 2000PL | SabreLite™ 2000 Flashlight w/ Photoluminescent Shroud (Carded) |



**SabreLite™ 2000 Flashlight Specifications**

| Light Source | Tested Lumen Value | Tested Lux Value (@ 1 meter) |
|--------------|--------------------|------------------------------|
| Xenon        | 33.0               | 10,000                       |

  

| Batteries                   | Battery Burn Time | Battery Pack/Charging Time |
|-----------------------------|-------------------|----------------------------|
| 3 C Alkaline (Not included) | 5 hrs.            | N/A                        |

  

| Watts | Voltage |
|-------|---------|
| 3.3   | 4.5     |

  

| Length          | Weight w/Batteries | Weight w/o Batteries |
|-----------------|--------------------|----------------------|
| 7.79" (19.8 cm) | 12.8 oz. (0.36 kg) | 5.31 oz. (0.15 kg)   |

**SabreLite™ 2000 Flashlight Approvals**

|  |  |
|--|--|
|  | Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.                           |
|  | Class I, II, Div. 2; Gp. ABCD/G , T3C.   |
|  | Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C |
|  | 10C-629-2  |
|  | IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67  |

**SabreLite™ 2000 Flashlight Accessories**

| Cat. # | Description | Sug. Retail |
|--------|-------------|-------------|
|--------|-------------|-------------|

|        |                             |           |
|--------|-----------------------------|-----------|
| 2004   | SabreLite™ 2000 Lamp Module | US\$13.50 |
| 2003PL | Photoluminescent Shroud     | US\$8.95  |
| 8052OR | Traffic Wand (Orange)       | US\$11.50 |
| 8052YW | Traffic Wand (Yellow)       | US\$11.50 |

**Pelican™ Products, Inc.**

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)