

# X-Tractor C Combination Tool

# MOC Combi

## Model 362R482

Compact, lightweight and powerful: three words that accurately describe the multi-functional X-Tractor C combination tool. Weighing in at 40 pounds, this tool easily performs both cutting and spreading functions at time critical rescue scenes.

### Applications



- Vehicle rescue applications
- Urban search and rescue operations
- Industrial rescue applications
- Structural collapse
- Large-scale rescue situations including train wrecks, aircraft emergencies and large truck/tractor accidents

### Features & Benefits

- Two tools in one - this unit features both spreading and cutting capability in a single integrated tool design
- Premium quality components, including a heat-treated alloy steel piston & piston rod; machined alloy cylinder body; and heat treated forged alloy steel regrindable blades
- Lightweight and compact
- Easy operation
- Precise fingertip operation in any position
- Star-grip control valve actuator permits tool operation from almost any handling position

## Model 362R483

The MOC Combination tool is both powerful and multifunctional. Featuring up to 43,388 lbs. of spreading force, up to 17,535 lbs. of pulling force and up to 120,272 lbs. of cutting force, the MOC Combi easily gets the job done with power to spare.

### Applications

- Vehicle rescue applications
- Urban search and rescue operations
- Remote rescue
- Structural collapse
- Large-scale rescue situations including train wrecks, aircraft emergencies and large truck/tractor incidents
- Industrial rescue

### Features & Benefits

- Features up to 43,388 lbs. of spreading force as well as up to 120,272 lbs. of cutting force
- Straight blade design that is well-suited for technical rescue operations
- Fast opening and closing action for increased speed during time-critical rescues
- Star-grip control valve actuator permits tool operation from almost any handling position



- Dropped forged shock resistant steel blades
- Two tools in one: spreader and cutter
- Premium quality components
- Star-grip control valve
- Dual pilot check valve



**NFPA 1936**  
Compliant  
**—2005—**

X-TRACTOR C  
362R482

MOC COMBI  
362R483

Specifications	Model 362R482	Model 362R483
Description	X-Tractor C	MOC Combi
Spreading Force	up to 24,279 lbs.	up to 43,388 lbs.
Spreading Distance	14.1"	16.72"
Cutting Force	up to 81,381 lbs.	up to 120,272 lbs.
Pulling Force	up to 10,554 lbs.	up to 17,535 lbs.
Max. Cutting Width	10.43"	10.43"
Cutter Opening	10.5"	12.23"
Size (L x W x H)	30.3 x 11 x 7.3 in.	34.01 x 9.26 x 7.54 in.
Weight	40 lbs.	48 lbs.